

### AMENDMENTS TO THE CLAIMS

1. (Currently Amended) A cut-resistant composite comprising:

- a matrix, provided on at least one side with a fabric, ~~said fabric, comprising at least two layers and/or at least two directions of individual elements of which at least one individual element is reinforced and which elements are interconnected by chemicals, plastics, rubbers and/or by connection elements which connection is weaker than the reinforced element, and~~
- at least one insulating layer interposed between said matrix and said fabric;

wherein said fabric is cut resistant to a force of more than 10 Newton and consists of two, three, four or more individual layers of metal or steel thread containing reinforcement elements, that are not interwoven but have an indirect connection created by a stitching, tufting or knitting yarn which is weaker than the reinforcement element, said individual layers of reinforcement elements being superimposed onto each other and arranged under an angle with respect to each other which differs from 90°.

2. (Currently Amended) A cut-resistant composite comprising:

- a matrix, provided on at least one side with a fabric, ~~said fabric comprising at least two individual layers of reinforcement elements whereby in each of said individual layers all reinforcement elements are provided in only one same direction, said individual layers being interconnected or deposited onto each other, and~~
- at least one insulating layer interposed between said matrix and said fabric;

wherein said fabric is cut resistant to a force of more than 10 Newton and consists of two, three, four or more individual layers of metal or steel thread containing reinforcement elements, that are not interwoven but have an indirect connection created by a stitching, tufting or knitting yarn which is weaker than the reinforcement element, said individual layers of reinforcement elements being superimposed onto each other and arranged under an angle with respect to each other which differs from 90°, and whereby in each of said individual layers all reinforcement elements are provided in only one same direction.

Appl. No. : 10/661,004  
Filed : September 11, 2003

3. **(Currently Amended)** The composite according to claim 1, whereby said fabric comprises free spaces between the individual elements, and whereby ~~preferably~~ the volume of said free spaces in said fabric is greater than the volume of the individual elements.

4. **(Currently Amended )** The composite according to claim 3, whereby the volume of the free spaces in said fabric is comprised between 3% and 99%, ~~preferably is more than 25%, and more preferably more than 50%~~ of the total volume of said fabric.

5. **(Original)** The composite according to claim 1, comprising at least two insulating layers whereby at least one layer is provided on one side of said fabric, and at least one other layer is provided on the other side of said fabric.

6. **(Original)** The composite according to claim 5, wherein at least one insulating layer is able to act as a positive electrical conductor, and wherein at least one other insulating layer is able to act as a negative or neutral electrical conductor.

7. **(Original)** The composite according to claim 6, wherein the connection between said positive with said negative or neutral electrical conductor is capable of activating an alarm signal.

8. **(Original)** The composite according to claim 1, further comprising at least one insulating layer, whereby said layer is provided between two layers and/or two directions of individual elements of said fabric.

9. **(Original)** The composite according to claim 1, wherein the insulating layer and the matrix are made of material selected from the group consisting of silicone, a metal foil, damped or sputtered metal foil, rubber, and a polymer which is selected from the group consisting of PVC, polyester, polypropylene, polyamide, polyethylene, ethylene/butene copolymers (PEB), poly ethylene terephthalate (PET), polybutyl teraphthalate (PBT), polyvinylidifluoride (PVDF), poly urethane (PU), and chlorinated PVC (PVCC), or other polymers or mixtures thereof.

Appl. No. : 10/661,004  
Filed : September 11, 2003

10. **(Original)** The composite according to claim 1, whereon at least one side of said composite is provided with an adhesive layer.

11. **(Original)** The composite according to claim 10, wherein said adhesive layer is self-adhesive, optionally with a releasing back sheet.

12. **(Original)** The composite according to claim 11, wherein said adhesive layer is electro-conductive.

13. **(Currently Amended)** The composite according to claim 1, wherein at least one of the reinforcement individual elements is ~~partly or wholly~~ electro-conductive and ~~at least partly~~ insulated.

14. **(Currently Amended)** The composite according to claim 13, wherein said electro-conductive material is selected from the group ~~consist~~ consisting of a metal thread, a conductive fiber, a conductive polymer, aluminum foil, damped and/or sputtered metals, damped and/or sputtered aluminum foil, and mixtures thereof.

15. **(Cancelled)**

16. **(Original)** The composite according to claim 13, wherein the insulating material is selected from the group consisting of silicone, rubber, PVC, polyester, polypropylene, polyamide, polyethylene, ethylene/butene copolymers (PEB), poly ethylene terephthalate (PET), polybutyl teraphthalate (PBT), polyvinylidifluoride (PVDF), poly urethane (PU), chlorinated PVC (PVCC), and mixtures thereof.

17. **(Original)** The composite according to claim 1, wherein the reinforcement elements in the fabric have an indirect connection with the insulating layer, said connection being created by chemicals, plastics, rubbers or by connection elements, such that the connection force between said elements and said layer is weaker than the reinforcement elements.

Appl. No. : 10/661,004  
Filed : September 11, 2003

18. **(Original)** The composite according to claim 1, wherein the reinforcement elements in said fabric consist of single ends.

19. **(Currently Amended)** The composite according to claim 1, wherein the reinforcement ~~reinforced~~ element is provided with joints or weakening points for enabling folding of the composite.

20. **(Original)** The composite according to claim 1, wherein said composite is selected from the group consisting of a tarpaulin; a cover; a canvas; a "convertible" for cars or other transport vehicle; a luggage or a parcel or another packing material; an upholstery composite reinforced in the form of seats chairs; a flexible in preference but also non-flexible door; a shelter and/or tent; a temporary wall or fence as used for exhibition rooms; a tape or zipper or other fastening means, preferably self-adhesive tape; a rope; a filter; and a gas absorber or liquid absorber suitable for use in the cabin of a vehicle for preventing the entry of toxic gases in said cabin.